





F3150046 - Bronze

 $Floor\ lamp\ providing\ diffused\ light.\ Extruded\ aluminium\ frame\ 10x10x1\ gratin\'e\ and\ anodized\ in\ various\ finishes.$ Leds on the top edges incorporated in the extrusions and burnished into the resin, guaranteeing the IP level. ${\sf ON/OFF} \ {\sf switch} \ {\sf in} \ {\sf the} \ {\sf IP} \ {\sf box} \ {\sf containing} \ {\sf the} \ {\sf drivers}. \ {\sf Two-pole} \ {\sf spark-proof} \ {\sf schukoplug}.$


Main specifications

Power (W)	15	Environment	Outdoor wet location
CCT (K)	3500K		

CRI 85 Net lumen (lm) N/D Mountings Floor



Lighting type	Direct
LED type	LED Module
Light distribution	Symmetric
Optical type	Diffused light



Luminous flux luminaire

Beam	Angle:	73°
h(m)	E(l x)	D(m
1	337	1.49
2	84	2.98
3	37	4.47
4	21	5.96
5	13	7.44






Frequency (Hz)	50/60
Voltage (V)	100-240
Lamp holder	LED Module
Emergency	Without
Insulation class	II

Physical

Color Bronze Weight (kg) 1.15













IPNOS OUTDOOR Anodized Bronze



Ipnos Top Plate F3125000