


## IPNOS OUTDOOR Anodized Natural

■ F3150054 - Anodized Natural

Floor lamp providing diffused light. Extruded aluminium frame 10x10x1 gratiné and anodized in various finishes. Leds on the top edges incorporated in the extrusions and burnished into the resin, guaranteeing the IP level. ON/OFF switch in the IP box containing the drivers. Two-pole spark-proof schuko plug.




### Main specifications

<b>Power (W)</b>	15	<b>Environment</b>	Outdoor wet location
<b>CCT (K)</b>	3500K		
<b>CRI</b>	85		
<b>Net lumen (lm)</b>	N/D		
<b>Mountings</b>	Floor		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED Module
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Diffused light



Beam Angle: 73°

h(m)	E(lx)	D(m)
1	337	1.49
2	84	2.98
3	37	4.47
4	21	5.96
5	13	7.44

Luminous flux luminaire  
744 lm




### Electrical

<b>Frequency (Hz)</b>	50/60
<b>Voltage (V)</b>	100-240
<b>Lamp holder</b>	LED Module
<b>Emergency</b>	Without
<b>Insulation class</b>	II

### Physical

<b>Color</b>	Anodized Natural
<b>Weight (kg)</b>	1.15



## IPNOS OUTDOOR Anodized Natural



---

It's a transparent methacrylate diffuser, designed to be placed on the top of the fitting with the possibility to bear up to 5 kg. The Top Plate is adaptable for Ipnos both indoor and outdoor version.

F3125000