



KTribe F3 Outdoor Green wall

F6268041 - Green Wall

Floor lamp emitting diffused light for outdoor use. Die-cast aluminum base and pole support. Chemical conversion treatment of the structural parts to enhance their resistance to atmospheric agents. Chrome finish. Injection-molded polycarbonate internal diffuser and bulb-holder. External diffuser made from braided colored PVC tubes and inner frame from polyester-painted aluminum tubes. Steel cathaphoresis treated counterweight for effective weather resistance. Painted die-cast aluminum external diffuser cover.


Main specifications

Mountings	Floor
Environment	Outdoor wet location



Optical

Lighting type	Direct
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	85
Beam angle C90-270 (°)	85



Beam Angle DIR: 82°

h(m)	E(lx)	D(m)
1	156	1.74
2	39	3.49
3	17	5.23
4	10	6.98
5	6	8.72

Luminous flux luminaire
4350 lm

Electrical

Frequency (Hz)	50-60
Voltage (V)	220-240
Emergency	Without
Insulation class	II

Physical

Color	Green Wall
Orientation	Fixed
Weight (kg)	23

Note

Light source not included. HSGS E27: 1x250W or 1 LED: 21W - 2450 lm - 3000K
We recommend using a connection system with a degree of protection greater than or equal to the degree of protection of the luminaire.

