

KTribe F3 Outdoor Panama

F6268022 - Panama

Floor lamp emitting diffused light for outdoor use. Die-cast aluminum base and pole support. Chemical conversion treatment of the structural parts to enhance their resistance to atmospheric agents. Chrome finish. Injection-molded polycarbonate internal diffuser and bulb-holder. External diffuser made from braided colored PVC tubes and inner frame from polyester-painted aluminum tubes. Steel cataphoresis treated coun-terweight for effective weather resistance. Painted die-cast aluminum external diffuser cover.

Main specifications

Number of heads	1
Power (W)	230
Mountings	Floor
Environment	Outdoor wet location

Optical

Lighting type	Direct
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	85
Beam angle C90-270 (°)	85



Luminous flux luminaire
4350 lm

Beam Angle DIR: 85°

h(m)	E(lx)	D(m)
1	195	1.82
2	49	3.64
3	22	5.46
4	12	7.28
5	8	9.10

Electrical

Frequency (Hz)	50/60
Voltage (V)	220-250
Lamp holder	E27
Emergency	Without
Insulation class	II

Physical

Color	Panama
Orientation	Fixed
Weight (kg)	24

Note

Light source not included. HSGS E27: 1x250W or 1 LED: 21W - 2450 lm - 3000K
We recommend using a connection system with a degree of protection greater than or equal to the degree of protection of the luminaire.