

## Landlord Soft PWM Dimmable Anodized Black

■ F004H40A071 - Anodized Black



IP65 projector for external use, designed to offer diffuse lighting.

It is characterized by an aluminium disk shape head, orientable up to 20° beam and lockable in position, to be powered at 24V, and available in 2700K, 3000K and 4000K colour temperature.

It is the perfect tool to light bushes, flowerbed and transit areas with an homogenous diffuse light beam.

Landlord Soft can be installed on solid ground spikes, with the possibility of an optional picket.

20° adjustable head for installation on ground poles.

Poles to be ordered as separated accessories.

24V remote power supply to be ordered separately.

Each head comes with a 2000 mm lenght outgoing cable and a wiring kit.

### Main specifications

<b>Lamp category</b>	LED	<b>Mountings</b>	Ground
<b>Power (W)</b>	5	<b>Environment</b>	Outdoor wet location
<b>CCT (K)</b>	4000K		
<b>CRI</b>	80		
<b>Net lumen (lm)</b>	269		

### Optical

<b>Lighting type</b>	Direct	<b>Beam angle C90-270 (°)</b>	51
<b>LED type</b>	Top LED		
<b>Light distribution</b>	Symmetric		
<b>Optical type</b>	Diffused light		
<b>Beam angle (°)</b>	51		

### Electrical

<b>Frequency (Hz)</b>	50-60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	24	<b>Insulation class</b>	III
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote excluded		
<b>Driver type</b>	Dimmable DALI PWM, Dimmable 1-10 PWM		

### Physical

<b>Color</b>	Anodized Black
<b>Orientation</b>	Adjustable
<b>Weight (kg)</b>	0.40
<b>Rotation (°)</b>	359

### Note


Carefully install and maintain the fixtures to avoid damaging the coating.

For LED fixtures, most problems are tied to electrical issues related to the insulation, which may cause destructive electrical discharges.

These are frequently caused by:

- power surges from the power network where fixture is connected.
- electrostatic discharge (ESD) from the environment.

We recommend installing a power-surge protection device on the fixture to reduce the intensity of these effects and prevent irreversible damages. The specific device should be chosen based on the electrical characteristics.



## Landlord Soft PWM Dimmable Anodized Black



Power supply 120/270Vac / 24Vdc.35W  
Dimmable 1-10V PWM control. IP67  
F990B02A000



Power supply 24V 8W / 110-240V IP20  
Class II selv.\_Non Dimmable  
RF25754



Pole with base H 300 mm Anodized  
Black  
F004Z0D0071



Power supply 120/270Vac / 24Vdc.70W  
Dimmable 1-10V PWM control. IP67  
F990B04A000



Power supply 24V 8W / 110-240V IP65  
Class II selv. Non Dimmable  
RF25748



3/4 way terminal block 4 poles IP68  
H2O stop. (ø5,5÷12mm cable)  
F990C010000




1-10V PWM control interface 24Vdc  
120W. IP67. Power supply not included.  
F990B00A000



Power supply 24Vdc 20W / 110-240Vdc  
(15W@110V) IP67 Class II selv.  
Dimmable DALI  
RF26387



Earth stick  
F004Z060000



Wall base Anodized Black  
F004Z0A0071



2 way terminal block 4 poles IP68 H20  
stop. (ø5,5+12mm cable)  
F990C00A000



Power supply 24Vdc 70W / 220-240V  
IP67 Class II selv. Non Dimmable  
RF25749



Pole with base H 900 mm Anodized  
Black  
F004Z0F0071



Power supply 24Vdc 50W / 120-240V  
IP67 Class II selv. Non Dimmable  
RF25755



Power supply 120/270Vac / 24Vdc.70W  
Dimmable DALI PWM control. IP67  
F990B05A000



Power supply 24V 10W / 110-240V IP67  
Class II selv. Non Dimmable  
RF25757



Pole with base H 600 mm Anodized  
Black  
F004Z0E0071



Power supply 24V 10W / 110-240V IP20  
Class II selv. Non Dimmable  
RF25747



---

Power supply 120/270Vac / 24Vdc.35W  
Dimmable DALI PWM control. IP67  
F990B03A000



---

DALI PWM control interface 24Vdc  
120W. IP67. Power supply not included  
F990B01A000