

Leila 225 White Painted Frame Dimmable 1-10V

536058-310.1 - White



Round luminaire for installation in the ceiling – recessed.

Configuration: die-cast aluminium structure, EN AB-47100 alloy (low copper content) and AISI 316L stainless steel outer frame (raw or painted in white). Glass diffuser: textured with silkscreen border, fixed to the aluminium structure through a robotic gluing system.

Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sandblasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting.

Protection rating: IP66

In compliance with EN60598-1 standards

Class of insulation: II; version 230V: I

Installation: the luminaire is equipped with a watertight M12 screw-connector providing optimal insulation against water ingress. 220-240V version: the luminaire is supplied with a remote IP67 electronic power supply kit equipped with a piece of cable with screw connector towards the luminaire and a piece of cable to be used for wiring. 230V direct feeding: the luminaire is equipped with a piece of cable with a 2-way connector for 3-conductor cables (H2O STOP) for an easy-to-make connection. Outdoor use requires suitable flexible cables assuring the watertightness of the cable gland / connector.

We recommend the use of a connection system with a protection degree greater than or equal to the protection degree of the luminaire.

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating.

Damages on the coating exposed to outdoor conditions or water, could cause corrosion.




Chemical substances affect the anticorrosion covering protection.

Main specifications

Power (W)	38	Mountings	Ceiling recessed
System power (W)	43	Environment	Outdoor
CCT (K)	3000K		
CRI	80		
Net lumen (lm)	3256		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Asymmetric
Optical type	Medium



Electrical

Frequency (Hz)	50-60	Insulation class	II
Voltage (V)	220-240		
Dimmable	Yes		
Driver type	Electronic dimmable 1-10V		
Emergency	Without		

Physical

Color	White
-------	-------

Leila 225 White Painted Frame Dimmable 1-10V




Box for Ceiling Recessed Installation
Leila 225
199



3/4 Way Terminal Block 4 Poles Ip68
H2O Stop
215



2 Way Terminal Block 4 Poles Ip68 H2O
Stop
236



SPD (Surge Protection Device)
237