
# FLOS







### Leo 80 Power Led Unidirectional

12316450.18 - Deep Brown

Luminaire for installation on wall – surface mounted.

Configuration: die-cast aluminium structure, EN AB-47100 alloy (low copper content). Diffuser: transparent glass or lens with silkscreen border.

Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders that are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components that have been sandblasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. Protection rating: IP65

In compliance with EN 60598-1 standards

Class of insulation: I

Installation: wiring through a cable holder (5mm<Ø<9mm cable). Outdoor use requires suitable flexible cables assuring the watertightness of the cable holder. For watertightness to be assured the use of a multicore cable is mandatory, the use of single unipolar cables is not allowed.

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating.

Damages on the coating exposed to outdoor conditions or water, could cause corrosion.

Chemical substances affect the anticorrosion covering protection.

#### Main specifications

Main specifications			
Power (W) System power (W) CCT (K) CRI Net lumen (Im)	1.1 2.5 4000K 80 28	Mountings Environment	Wall surface Outdoor
Optical			
Lighting type LED type Light distribution Optical type	Direct Power LED Symmetric Medium	90* 60* 30*	m lux Max lux Max lux Med   1.00 45 34   2.00 11 9   3.00 5 4   4.00 3 2   \$5.00 2 1

- C0 / C180

Insulation class

···· C90 / C270

 $\alpha = 20.0^{\circ} + 20.0^{\circ}$ 

I

#### Electrical Frequency (Hz) Voltage (V)

Dimmable Driver type Emergency

Physical <sub>Color</sub>

Deep Brown

Not dimmable

50-60

No

100-240

Without

https://flos.com/professional-space/outdoor/products/leo-80-power-led-unidirectional-12316450.18/

β = 25.0°+ 25.0°

## Leo 80 Power Led Unidirectional



SPD (Surge Protection Device) 237