

Maxi Martina Aqua 24V

105211145.0 - Inox

Adjustable spotlight.

Configuration: AISI 316L stainless steel structure and adjustable bracket. Glass diffuser: transparent or sandblasted with silkscreen border, fixed through a robotic gluing system.

Protection rating: IP68

In compliance with EN60598-1 standards

Class of insulation: III

Installation: the luminaire is equipped with 5000mm cable. Martina Aqua 24V and Maxi Martina Aqua 24V are equipped with a dc/dc highly efficient resin-coated converter that removes electromagnetic interference and protects against polarity reversal and sudden voltage peak. Parallel wiring required. Mini Martina Aqua, Martina Aqua RGB and Maxi Martina Aqua RGB requires connection in series. SELV equivalent remote power supply required.

We recommend the use of a connection system with a protection degree greater than or equal to the protection degree of the luminaire.

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating.

 ${\sf Damages} \ on \ the \ coating \ exposed \ to \ outdoor \ conditions \ or \ water, \ could \ cause \ corrosion.$


Chemical substances affect the anticorrosion covering protection.

Main specifications

Power (W)	9.9	Mountings	Ceiling, Ground, Wall surface
System power (W)	14.7	Environment	Outdoor
CCT (K)	4000K		
CRI	80		
Net lumen (lm)	723		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium



Electrical

Frequency (Hz)	50-60	Insulation class	Ш
Voltage (V)	24		
Dimmable	No		
Driver type	Not dimmable		

Without

Physical

Emergency

Color Inox

Maxi Martina Aqua 24V







Ground Spike Martina/Mini Martina/Perseo 9/lota 136

3/4 Way Terminal Block 4 Poles Ip68 H2O Stop 215

2 Way Terminal Block 4 Poles Ip68 H2O Stop 236





Power Supply 50W 120÷240V/24Vdc lp67 155 Power Supply 70W 220÷240V/24Vdc lp67 110