

## Maxi Martina Rgb

10525600.1 - White

Adjustable spotlight.

Configuration: turned and anodized (raw or painted) aluminium structure with stainless steel adjustable bracket. Glass diffuser: transparent or sandblasted with silkscreen border, fixed through a robotic gluing system. Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting.

Protection rating: IP67

In compliance with EN60598-1 standards

Class of insulation: III

Installation: the luminaire is equipped with 2000mm cable. Martina 24V and Maxi Martina 24V are equipped with a dc/dc highly efficient resin-coated converter that removes electromagnetic interference and protects against polarity reversal and sudden voltage peak. Parallel wiring required. Mini Martina, Martina RGB and Maxi Martina RGB requires connection in series.

We recommend the use of a connection system with a protection degree greater than or equal to the protection degree of the luminaire.

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating.

Damages on the coating exposed to outdoor conditions or water, could cause corrosion.

Chemical substances affect the anticorrosion covering protection.

### Main specifications

<b>Power (W)</b>	13.6
<b>System power (W)</b>	13.6
<b>Mountings</b>	Ceiling, Ground, Wall surface
<b>Environment</b>	Outdoor

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Medium

### Electrical

<b>Frequency (Hz)</b>	50-60
<b>Dimmable</b>	Yes
<b>Driver type</b>	Dmx
<b>Emergency</b>	Without
<b>Insulation class</b>	III

### Physical

<b>Color</b>	White
--------------	-------

## Maxi Martina Rgb



Ground Spike Martina/Mini  
Martina/Perseo 9/Iota  
136




Power Supply Dmx Rgb 36W  
220÷230V/3Chx350mA Ip67  
141



Dmx Controller Dimmer Switch For  
Recessed Box  
142



Dmx Controller Stand-Alone/Pc  
Interface  
143



DMX splitter 512 – electronic device to  
regenerate the monodirectional DMX  
signal 1 Input and 7 output, 12-  
24Vdc\_IP20. Power supply not included  
187



Dmx Cable Shielded Twisted Pair  
186