
FLOS







Maxi Melrie Mid-Power Led Bidirectional

4827522.6 - Grey

Luminaire for installation on wall – surface mounted.

Configuration: polycarbonate structure and die-cast aluminium cover and base (MaxiMelrie only), EN AB-47100 alloy (low copper content)

Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders that are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components that have been sandblasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. Protection rating: IP65

In compliance with EN 60598-1 standards

Class of insulation: Melrie: II; MaxiMelrie: I

Installation: Melrie: wiring through two rubber cable holders (5mm<0<10mm cables); MaxiMelrie: wiring through two rubber cable holders (8mm<0<13mm cables). Outdoor use requires suitable flexible cables assuring the watertightness of the cable holder.

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating.


Damages on the coating exposed to outdoor conditions or water, could cause corrosion.

Chemical substances affect the anticorrosion covering protection.

Main specifications

Main specifications							
Power (W) System power (W) CCT (K) CRI	17.6 18 3000К 80	Mountings Environment	Wall surface				
			Outdoor				
Net lumen (lm)	2X778						
Optical							
Lighting type LED type	Indirect, Direct Power LED	120*	m	lux lux Max Med			

LED type Light distribution Optical type Indirect, Direct Power LED Symmetric Diffused light



Electrical				
Frequency (Hz) Voltage (V) Dimmable Driver type Emergency	50-60 220-240 No Not dimmable Without	Insulation class	1	
Physical				
Color	Grey			

Note

Dimmable version on request

Maxi Melrie Mid-Power Led Bidirectional



SPD (Surge Protection Device) 237