

Melrie Bidirectional

481122.6 - Grey

Luminaire for installation on wall - surface mounted.

Configuration: polycarbonate structure and die-cast aluminium cover and base (MaxiMelrie only), EN AB-47100 alloy (low copper content)

Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders that are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components that have been sandblasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting.

In compliance with EN 60598-1 standards

Class of insulation: Melrie: II; MaxiMelrie: I

Installation: Melrie: wiring through two rubber cable holders (5mm< \emptyset <10mm cables); MaxiMelrie: wiring through two rubber cable holders (8mm< \emptyset <13mm cables). Outdoor use requires suitable flexible cables assuring the watertightness of the cable holder.

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating.

Damages on the coating exposed to outdoor conditions or water, could cause corrosion.

Chemical substances affect the anticorrosion covering protection.


Main specifications

Power (W) 40 Mountings Wal

MountingsWall surfaceEnvironmentOutdoor

Optical

Lighting type Indirect, Direct
Light distribution Symmetric
Optical type Diffused light



Electrical

 Frequency (Hz)
 50-60
 Emergency
 Without

 Voltage (V)
 220-240
 Insulation class
 II

 Lamp holder
 E14

 Dimmable
 No

Not dimmable

Physical

Driver type

Color Grey