

Memi

496000.3 - Anthracite

Luminaire for installation on wall – surface mounted.
Configuration: die-cast aluminium structure, EN AB-47100 alloy (low copper content). Glass diffuser: sandblasted.
Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders that are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components that have been sandblasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting.
Protection rating: IP65
In compliance with EN 60598-1 standards
Class of insulation: I
Installation: wiring through M16 plastic cable gland (4,5mm<Ø<10mm cables). Outdoor use requires suitable flexible cables assuring the watertightness of the cable gland.
During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating.
Damages on the coating exposed to outdoor conditions or water, could cause corrosion.
Chemical substances affect the anticorrosion covering protection.

Main specifications

Power (W)	2X18
Mountings	Wall surface
Environment	Outdoor

Optical

Lighting type	Direct
Light distribution	Asymmetric
Optical type	Diffused light





Electrical

Frequency (Hz)	50-60	**Emergency**	Without
Voltage (V)	220-240	**Insulation class**	I
Lamp holder	G24q-2		
Dimmable	No		
Driver type	Not dimmable		

Physical

Color	Anthracite