

Midna Bidirectional Mid-Power Led Dimmable Dali

529008-300.12 - Forest Green

Luminaire for installation on wall – surface mounted.

Configuration: polycarbonate structure and die-cast aluminium cover and base, EN AB-47100 alloy (low copper content)

Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders that are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components that have been sandblasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting.

In compliance with EN 60598-1 standards

Class of insulation: I

Installation: wiring through two cable holders ($8mm < \emptyset < 13mm$ cables). Outdoor use requires suitable flexible cables assuring the watertightness of the cable holder.

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating.

Damages on the coating exposed to outdoor conditions or water, could cause corrosion.

Chemical substances affect the anticorrosion covering protection.

2X763

Main specifications

| Power (W) | 17.6 | Mountings | Wall surface |
|------------------|-------|-------------|--------------|
| System power (W) | 19 | Environment | Outdoor |
| CCT (K) | 3000K | | |
| CRI | 80 | | |

Optical


Net lumen (lm)

 Lighting type
 Indirect, Direct

 LED type
 Power LED

 Light distribution
 Symmetric

 Optical type
 Diffused light



Electrical

Frequency (Hz) 50-60 Insulation class
Voltage (V) 220-240
Dimmable Yes
Driver type Electronic


Without

dimmable DALI

Emergency Physical

Color Forest Green

Midna Bidirectional Mid-Power Led Dimmable Dali



SPD (Surge Protection Device) 237