









Midna Unidirectional Mid-Power Led

5

529004.18 - Deep Brown

Luminaire for installation on wall - surface mounted.

Configuration: polycarbonate structure and die-cast aluminium cover and base, EN AB-47100 alloy (low copper content)

Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders that are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components that have been sandblasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting.

In compliance with EN 60598-1 standards

Class of insulation: I

Installation: wiring through two cable holders (8mm< \emptyset <13mm cables). Outdoor use requires suitable flexible cables assuring the watertightness of the cable holder.

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating.

Damages on the coating exposed to outdoor conditions or water, could cause corrosion.

Chemical substances affect the anticorrosion covering protection.

Main specifications

Power (W)	8.8	Mountings	Wall surface
System power (W)	11	Environment	Outdoor
CCT (K)	3000K		
CDI	90		

Optical

Net lumen (lm)

 Lighting type
 Direct


 LED type
 Power LED

 Light distribution
 Symmetric

 Optical type
 Diffused light



Insulation class



Electrical Frequency (Hz)

Voltage (V)	220-240
Dimmable	No
Driver type	Not dimmable
Emergency	Without

50-60

Physical

Color Deep Brown

Midna Unidirectional Mid-Power Led



SPD (Surge Protection Device) 237