

## Outgraze 50 Easy L 900 mm Dimmable DALI White

□ F021J4LD001 - White




Luminaire for outdoor use for installation on the wall or ceiling with LED light source.  
 Central body in extruded aluminum, end cap in die-cast aluminum.  
 Optics made with constant pitch between the lenses to offer a homogeneous luminous flux even in case of multiple lamps installed in a continuous line.  
 High resistance external coating applied with a double layer of epoxy powders in accordance with the QUALICOAT standard. The first layer of epoxy powder gives chemical and mechanical resistance, the second finishing layer of polyester powder ensures resistance to UV rays and atmospheric agents.  
 The painted surfaces are treated with alkaline and acidic washes, then rinsed with demineralized water, subjected to a chemical conversion treatment to protect against oxidation.  
 Diffuser in sandblasted glass, screen-printed and glued to ensure a watertight seal.  
 The installation of the product requires use of steel brackets, to be ordered separately.  
 Integrated 120/240V power supply.  
 Continuous Line In/Out H2O Stop Version: prewired H2O Stop Plug&Play connectors for an easy in line connection (connecting accessory to be ordered separately).

### Main specifications

|                       |       |                    |                          |
|-----------------------|-------|--------------------|--------------------------|
| <b>Lamp category</b>  | LED   | <b>Mountings</b>   | Ceiling and wall surface |
| <b>Power (W)</b>      | 20    | <b>Environment</b> | Outdoor wet location     |
| <b>CCT (K)</b>        | 4000K |                    |                          |
| <b>CRI</b>            | 80    |                    |                          |
| <b>Net lumen (lm)</b> | 1092  |                    |                          |


### Optical

|                               |                |
|-------------------------------|----------------|
| <b>Lighting type</b>          | Direct         |
| <b>LED type</b>               | Power LED      |
| <b>Light distribution</b>     | Symmetric      |
| <b>Optical type</b>           | Diffused light |
| <b>Beam angle (°)</b>         | 90             |
| <b>Beam angle C90-270 (°)</b> | 90             |



|                    |              |             |  |
|--------------------|--------------|-------------|--|
| <b>Beam Angle:</b> | 80°          |             |  |
| <b>h(m)</b>        | <b>E(lx)</b> | <b>D(m)</b> |  |
| 1                  | 507          | 1.67        |  |
| 2                  | 127          | 3.34        |  |
| 3                  | 56           | 5.00        |  |
| 4                  | 32           | 6.67        |  |
| 5                  | 20           | 8.34        |  |

Luminous flux luminaire  
1092 lm



### Electrical

|                       |               |                         |         |
|-----------------------|---------------|-------------------------|---------|
| <b>Frequency (Hz)</b> | 50-60         | <b>Emergency</b>        | Without |
| <b>Voltage (V)</b>    | 120-240       | <b>Insulation class</b> | I       |
| <b>Dimmable</b>       | Yes           |                         |         |
| <b>Driver</b>         | Integrated    |                         |         |
| <b>Driver type</b>    | Dimmable DALI |                         |         |
|                       | 1             |                         |         |

### Physical

|                    |            |
|--------------------|------------|
| <b>Color</b>       | White      |
| <b>Orientation</b> | Adjustable |
| <b>Weight (kg)</b> | 3.30       |
| <b>Length (mm)</b> | 900        |

### Note


We recommend using a connection system with a degree of protection greater than or equal to the degree of protection of the luminaire.  
 During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating.  
 Damages on the coating exposed to outdoor conditions or water, could cause corrosion.  
 Chemical substances affect the anticorrosion covering protection.  
 For LED fixtures, there is evidence that most of the damages are connected to electrical effects related to the insulations, which cause destructive electrical discharges  
 These effects are frequently caused by:

- over voltage coming from the mains' network where fixture is connected.
- electrostatic discharge (ESD) coming from the environment.

The use of a protective device against the overvoltage on the electrical installation is warmly suggest this helps to reduce the intensity of some of these phenomenon and prevent irreversible damages. The selection of the type of device to be used must be adjust on the electrical plant.



## Outgraze 50 Easy L 900 mm Dimmable DALI White



One pair of long brackets L 200 mm.  
White  
F1204001



One pair of short brackets L 80 mm.  
White  
F1203001



Double 5-pole plug&play connector +  
5-pole cable, 600 mm length.  
F021Z050000



5-pole plug&play connector + 5-pole  
cable, 5000 mm length.  
F021Z060000



Plug&play connector 5 poles  
F021Z040000



4 way junction box 5 poles IP68 (6-14  
mm cables)  
F990C030000



Cap for panel (on the fixtures) plug  
connector 4-5 poles  
F021Z070000