


## Pointbreak Bollard 2 - 300

■ F023F4AD001 - White



Collection of outdoor bollards with an exclusive design and LED light source, characterized by a patented high-performance optics. The unique squircle shape is available in two sizes and three heights. The body structure comes in extruded aluminum, the head of the luminaire in cast aluminum, and the diffuser is made of transparent, UV-stabilized polycarbonate with scratch-resistant surface treatment. The optics integrated in the head allows an asymmetric, downward radial light emission that, combined with an aluminum reflector painted in absolute black, avoids indirect reflections in compliance with current light pollution laws. Available in different finishes with a double layer of powder coating and chemical conversion surface treatment to ensure high resistance against corrosion.

LED light source included. Integrated 220-240V ON/OFF and 1-10V/DALI dimmable electrical power. Equipped with a neoprene outlet cable and 2-way anti-condensation IP68 H2O Stop gasket. The luminaire may be easily installed on any type of floor with anchors. The anchoring plate for installation on flooring to be concreted must be ordered separately.


110V version upon request.

### Main specifications

|                 |       |                |        |
|-----------------|-------|----------------|--------|
| Number of heads | 1     | Net lumen (lm) | 672    |
| Lamp category   | LED   | Mountings      | Ground |
| Power (W)       | 12.5  |                |        |
| CCT (K)         | 4000K |                |        |
| CRI             | 80    |                |        |

### Optical

|                        |            |
|------------------------|------------|
| Lighting type          | Direct     |
| LED type               | Power LED  |
| Light distribution     | Asymmetric |
| Optical type           | Asymmetric |
| Beam angle (°)         | 34         |
| Beam angle C90-270 (°) | 106        |



Luminous flux luminaire  
672 lm

Beam Angle: 34°

## Pointbreak Bollard 2 - 300



---

Base plate with bolt  
F023Z060000