









Romeo Outdoor C3 Pvc (71 cm) Green wall

F6468041 - Green Wall

Suspension luminaire for outdoor use providing direct and diffused light. External diffuser obtained from braided colored PVC tubes, internal frame in polyester-painted aluminum tubes. Inner diffuser in opal-colored, vacuum-formed polycarbonate which is removable for bulb change without the use of tools. Diffuser support in anodized die-cast aluminum alloy, liquid grey painted. Die-cast aluminum alloy ceiling fitting with polished finish. Injection-molded polycarbonate (PC) cover rose. 316L stainless steel pole – polished.


In order to obtain good weather resistance, all the painted details have undergone a chemical conversion treatment for enhanced corrosion resistance.

Main specifications

Number of heads 1
Power (W) 250
Mountings Ceiling
Environment Outdoor wet location

Optical

Lighting type Direct
Light distribution Symmetric
Optical type Diffused light
Beam angle (°) 78
Beam angle C90-270 (°) 78



Luminous flux luminaire 2400 lm

| Beam A | ngle DIR | : 92° |
|--------|----------|-------|
| h(m) | E(lx) | D(m) |
| 1 | 182 | 2.07 |
| 2 | 46 | 4.15 |
| 3 | 20 | 6.22 |
| 4 | 11 | 8.29 |
| 5 | 7 | 10.36 |

Electrical

Frequency (Hz) 50/60
Voltage (V) 220-240
Lamp holder E27
Emergency Without
Insulation class

Physical

ColorGreen WallOrientationFixedWeight (kg)5.9

Note

Light source not included. HSGS E27: 1x250W or 1 LED: 21W - 2450 lm - 3000K

We recommend using a connection system with a degree of protection greater than or equal to the degree of protection of the luminaire.