



## Romeo Outdoor C3 Pvc (91 cm) Panama

 F6469022 - Panama

Suspension luminaire for outdoor use providing direct and diffused light. External diffuser obtained from braided colored PVC tubes, internal frame in polyester-painted aluminum tubes. Inner diffuser in opal-colored, vacuum-formed polycarbonate which is removable for bulb change without the use of tools. Diffuser support in anodized die-cast aluminum alloy, liquid grey painted. Die-cast aluminum alloy ceiling fitting with polished finish. Injection-molded polycarbonate (PC) cover rose. 316L stainless steel pole – polished.


In order to obtain good weather resistance, all the painted details have undergone a chemical conversion treatment for enhanced corrosion resistance.

### Main specifications

<b>Mountings</b>	Ceiling surface
<b>Environment</b>	Outdoor wet location

### Optical


<b>Lighting type</b>	Direct
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Diffused light
<b>Beam angle (°)</b>	74
<b>Beam angle C90-270 (°)</b>	74



Beam Angle DIR: 92°

h(m)	E(lx)	D(m)
1	182	2.07
2	46	4.15
3	20	6.22
4	11	8.29
5	7	10.36

Luminous flux luminaire  
2400 lm



### Electrical

<b>Frequency (Hz)</b>	50-60
<b>Voltage (V)</b>	220-240
<b>Emergency</b>	Without
<b>Insulation class</b>	I

### Physical

<b>Color</b>	Panama
<b>Orientation</b>	Fixed
<b>Weight (kg)</b>	7.5

### Note

Light source not included. HSGS E27: 1x250W or 1 LED: 21W - 2450 lm - 3000K

We recommend using a connection system with a degree of protection greater than or equal to the degree of protection of the luminaire.

