



## Sigma cover 2 Beam

518252.0 - Inox

Round luminaire for installation on wall, ceiling or ground – recessed.

Configuration: turned aluminium body (EN AW-6060 alloy) with 15 micron anodizing for high resistance to corrosion. AISI 316L cap, open frame and cover. Diffuser: polycarbonate or methacrylate transparent or sandblasted (see the catalogue pages for reference).

Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sandblasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting.

Protection rating: IP67

In compliance with EN 60598-1 standards

Class of insulation: III

Installation: the luminaire is equipped with a piece of cable for an easy-to-make connection. In-ground version: the cable is integrated with an H20 STOP device. Sigma is equipped with a dc/dc highly efficient resin-coated converter that removes electromagnetic interference and is protected against polarity reversal and sudden voltage peak. Outdoor use requires suitable flexible cables. Installation in solid surfaces requires a dedicated box for installation to be purchased separately, installation in panels is only possible with the version with springs. It is important to provide for the in-ground version a >200mm gravel layer or a drain system (for concrete surfaces) to ensure good drainage and to avoid water stagnation.

Parallel wiring

We recommend the use of a connection system with a protection degree greater than or equal to the protection degree of the luminaire.

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating.

Damages on the coating exposed to outdoor conditions or water, could cause corrosion.



Chemical substances affect the anticorrosion covering protection.

### Main specifications

|                         |       |                    |                |
|-------------------------|-------|--------------------|----------------|
| <b>Power (W)</b>        | 2.2   | <b>Mountings</b>   | Floor recessed |
| <b>System power (W)</b> | 3.4   | <b>Environment</b> | Outdoor        |
| <b>CCT (K)</b>          | 2700K |                    |                |
| <b>CRI</b>              | 80    |                    |                |
| <b>Net lumen (lm)</b>   | 2X15  |                    |                |

### Optical

|                           |            |
|---------------------------|------------|
| <b>Lighting type</b>      | Direct     |
| <b>LED type</b>           | Power LED  |
| <b>Light distribution</b> | Asymmetric |
| <b>Optical type</b>       | Wide flood |



### Electrical

|                       |              |                         |     |
|-----------------------|--------------|-------------------------|-----|
| <b>Frequency (Hz)</b> | 50-60        | <b>Insulation class</b> | III |
| <b>Voltage (V)</b>    | 24           |                         |     |
| <b>Dimmable</b>       | No           |                         |     |
| <b>Driver type</b>    | Not dimmable |                         |     |
| <b>Emergency</b>      | Without      |                         |     |

### Physical

|              |      |
|--------------|------|
| <b>Color</b> | Inox |
|--------------|------|

### Note

Dimmable version on request


Sigma cover 2 Beam



Box for Installation Sigma  
170



Power Supply 8W 100+240Vac/24Vdc  
350mA Ip20  
150



Power Supply 100+240Vac/ 8W at  
24Vdc/ 6W at 350mA Ip65  
106



Power Supply 10W 110+240Vac/24Vdc  
Ip20  
87



Power Supply 10W 110+240Vac/24Vdc  
Ip67  
175



Power Supply 20W 220+240V/24Vdc  
Ip67  
147



Power Supply 50W 120+240V/24Vdc  
Ip67  
155



Power Supply 70W 220+240V/24Vdc  
Ip67  
110



2 Way Terminal Block 2 Poles Ip68 H2O  
Stop  
269