

## Talia h 360 mm Bidirectional

■ 503012.4 - Black

Bollard light.

Configuration: extruded aluminium structure. Polycarbonate diffuser: opal UV-stabilised.

Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sandblasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting.

Protection rating: IP65

In compliance with EN 60598-1 standards

Class of insulation: II

Installation: The LED module is housed in a sealed transparent polycarbonate cylinder with compensation valve.

The luminaire is equipped with a piece of cable and a wiring kit with crimp connectors and an adhesive heat-shrink tubing for a watertight electrical connection. We recommend installation on a concrete basement or surface, directly with bolts or through the dedicated fixing plate (to be ordered separately). Outdoor use requires suitable flexible cables.

We recommend the use of a connection system with a protection degree greater than or equal to the protection degree of the luminaire.

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating.

Damages on the coating exposed to outdoor conditions or water, could cause corrosion.



Chemical substances affect the anticorrosion covering protection.

### Main specifications

|                         |       |                    |         |
|-------------------------|-------|--------------------|---------|
| <b>Power (W)</b>        | 2x 3  | <b>Mountings</b>   | Pole    |
| <b>System power (W)</b> | 7     | <b>Environment</b> | Outdoor |
| <b>CCT (K)</b>          | 4000K |                    |         |
| <b>CRI</b>              | 80    |                    |         |
| <b>Net lumen (lm)</b>   | 2X73  |                    |         |

### Optical

|                           |                |
|---------------------------|----------------|
| <b>Lighting type</b>      | Direct         |
| <b>LED type</b>           | Power LED      |
| <b>Light distribution</b> | Symmetric      |
| <b>Optical type</b>       | Diffused light |



### Electrical

|                       |              |                         |    |
|-----------------------|--------------|-------------------------|----|
| <b>Frequency (Hz)</b> | 50-60        | <b>Insulation class</b> | II |
| <b>Voltage (V)</b>    | 220-240      |                         |    |
| <b>Dimmable</b>       | No           |                         |    |
| <b>Driver type</b>    | Not dimmable |                         |    |
| <b>Emergency</b>      | Without      |                         |    |

### Physical


|              |       |
|--------------|-------|
| <b>Color</b> | Black |
|--------------|-------|

## Talia h 360 mm Bidirectional



---

Base Plate and Fixing Bolts Talia  
139



---

SPD (Surge Protection Device)  
237