







Tau Tube 554 mm Transparent Diffuser

Light for installation on wall or ceiling - surface mounted.

Configuration: polycarbonate tube, opal or transparent, with anti-UV filter. Polycarbonate fixing brackets and anodized aluminium closing caps.

Protection Rating: IP65

In compliance with EN 60598-1 standards

Class of insulation: III

Installation: the luminaire is supplied with a screw connector and requires the use of a feeding cable (direct to power supply or for end-to-end connection) to be ordered separately. Parallel wiring required. Maximum end-to-end sequence: 5000mm.

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating.

Damages on the coating exposed to outdoor conditions or water, could cause corrosion.

Chemical substances affect the anticorrosion covering protection.

Main specifications

Power (W)	3
System power (W)	3
CCT (K)	3000K
CRI	80
Net lumen (lm)	384

Mountings Environment

Ceiling, Ground, Wall surface


Outdoor

Optical

Lighting type
LED type
Light distribution
Optical type

Direct
Power LED
Symmetric
Diffused light





Electrical

Frequency (Hz)	50-60
Voltage (V)	24
Dimmable	Yes
Driver type	Electronic
	dimmable
Emergency	Without

Insulation class

Tau Tube 554 mm Transparent Diffuser







Supply Cable Tau Tube L 2000 mm Single Connector 172

Supply Cable Tau Tube L 80 mm Double Connector 173

Supply Cable Tau Tube L 200 mm Double Connector 174







Power Supply 8W 100÷240Vac/24Vdc 350mA lp20 150

Power Supply 100÷240Vac/8W at 24Vdc/6W at 350mA lp65 106

Power Supply 10W 110÷240Vac/24Vdc lp20 87







Power Supply 10W 110÷240Vac/24Vdc Ip67 175

Power Supply 17W 110÷240V/24Vdc lp20 144

Power Supply 17W 110÷240V/24Vdc lp67 176







Power Supply Dali 20W 110÷240V/24Vdc lp67 252

Power Supply 20W 220÷240V/24Vdc lp67 147

Power Supply 50W 120÷240V/24Vdc lp67 155





Power Supply 70W 220÷240V/24Vdc lp67 110

Power Supply 96W 120÷277V/24Vdc lp67 156