



Midna High Efficiency Bidirectional Mid-Power Led Dimmable



529056-300.18 - Tiefbraun

Luminaire for installation on wall - surface mounted

Configuration: polycarbonate structure and die-cast aluminium cover and base, EN AB-47100 alloy (low copper

Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders that are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components that have been sandblasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting.

Protection rating: IP66

In compliance with EN 60598-1 standards

Class of insulation: I

Installation: wiring through two cable holders (8mm< \emptyset <13mm cables). Outdoor use requires suitable flexible cables assuring the watertightness of the cable holder.

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the

Damages on the coating exposed to outdoor conditions or water, could cause corrosion.


Chemical substances affect the anticorrosion covering protection.

Hauptspezifikationen

Leistung (W) Systemleistung (W)	17.6 19	Halterungen Umgebung	Wandoberfläche Außenbeleuchtung
CCT (K)	2700K		
CRI	80		
Nettolumen (lm)	2X815		

Optisch

Beleuchtungstyp Indirekt, Direkt LED-Typ Light distribution Leistungs-LED Symmetrisch Streulicht Optiktyp



Isolationsklasse

Elektrisch

Frequenz (Hz) 50-60 Spannung (V) 220-240 Dimmbar Yes Treiber-Typ Elektronisch dimmbar DALI Notfall

Ohne

Physikalisch

Farbe Tiefbraun β= 60.0°+ 60.0°

Midna High Efficiency Bidirectional Mid-Power Led Dimmable Dali



SPD (Surge Protection Device) 237