

Anna 410 Bicolour White/Yellow Dimmable Dali

533027-300 - White-Yellow

Outdoor / Indoor round luminaire for installation on ceiling or wall – surface mounted.

Configuration: opal plastic diffuser with satin finish for a high light emission uniformity ratio. Die-cast aluminium fixing back-plate and turned aluminium structure and heat sink. Magnetic finish frame to hide the fixing screws.

The luminaire is coated with polyester powders in single or double colour.

Protection rating: IP66

In compliance with EN 60598-1 standards

Class of Insulation: I

Installation: the luminaire is equipped with two IP65 cable holders for rubber cables $5 < \varnothing < 10\text{mm}$ (Anna Ø210 and Ø310) or cables $6 < \varnothing < 13\text{mm}$ (Anna Ø410) and a quick-connect 2-pole terminal block. Outdoor installation requires suitable flexible cables assuring the watertightness of the cable holder.

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating.

Damages on the coating exposed to outdoor conditions or water, could cause corrosion.



Chemical substances affect the anticorrosion covering protection.

Caractéristiques principales

Puissance (W)	27.9	Fixations	en applique plafond, En applique murale
Puissance du système (W)	34	Environnement	per esterni
CCT (K)	3000K		
IRC	80		
Lumen net (lm)	2712		

Optique

Type d'éclairage	Direct
type de LED	Power LED
Light distribution	Symétrique
Type d'optique	Lumière diffuse




Electrique

Fréquence (Hz)	50-60	Classe d'isolation	I
Tension (V)	220-240		
Dimmable	Oui		
Type de driver	Electronique dimmable DALI		
Urgence	Sans		

Physique

Coloris	White-Yellow
----------------	--------------

Anna 410 Bicolour White/Yellow Dimmable Dali



SPD (Surge Protection Device)

237