


## Light Shadow Pro Ø 60 Adjustable Optic Flood

New

03.9933.06 - Chrome

LED lighting module, with low glare, to be inserted in the recessed frames (not included), installation through a bayonet system with interchangeable spots. Remote driver not included.




## Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 677                 |
| Lamp category   | LED   | Mountings      | Recessed            |
| Power (W)       | 10,5W | Environment    | Indoor dry location |
| CCT (K)         | 4000K |                |                     |
| CRI             | 90    |                |                     |

## Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Flood     |
| Beam angle (°)         | 28        |
| Beam angle C90-270 (°) | 28        |



Beam Angle: 28°

h(m) E(lx) D(m)

1 2668 0.50

2 667 0.99

3 296 1.49

4 167 1.98

5 107 2.48

Luminous flux luminaire  
677 lm

## Electrical

|              |                                                                                                                       |                  |     |
|--------------|-----------------------------------------------------------------------------------------------------------------------|------------------|-----|
| Current (mA) | 300                                                                                                                   | Insulation class | III |
| Dimmable     | Yes                                                                                                                   |                  |     |
| Driver       | Remote excluded                                                                                                       |                  |     |
| Driver type  | Non Dimmable, Dimmable DALI 2, Dimmable, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1, Mains Cut Dimming Without |                  |     |
| Emergency    | Without                                                                                                               |                  |     |

## Physical

|                     |            |                    |     |
|---------------------|------------|--------------------|-----|
| Color               | Chrome     | Rotation (°)       | 355 |
| Orientation         | Adjustable | Spot diameter (mm) | 60  |
| Recessed depth (mm) | 93         |                    |     |
| Weight (kg)         | 0.22       |                    |     |
| Tilt (°)            | 30         |                    |     |

## Light Shadow Pro Ø 60 Adjustable Optic Flood



Installation Frame Trim  
08.0164.14

Non dimmable continuous current power supply of 220/240V – 50/60Hz with power current selected through adjustable with switch 200 mA – 8,5W / 300 mA – 13W / 350 mA – 15W / 400 mA – 17,5W / 450 mA – 19,5W / 500 mA – 22W  
60.9160

Continuous current power supply, 0/1-10V dimmable, 220/240V – 50/60Hz, 300mA-16W / 350mA-18W / 400mA-21W / 500mA-27W / 600mA-32W / 650mA-35W / 700/750/800/900/950/1000/1050mA-36W  
60.9439



Continuous current supply source 240V – 50/60Hz with dimmable DALI 2, push dimming. 300mA-16W / 350mA-18W / 400mA-21W / 500mA-27W / 600mA-32W / 650mA-35W / 700/750/800/900/950/1000/1050mA-38W  
60.9186

Installation Frame Trim  
08.0164.40

Continuous current power supply of 13-20W, 110/240V – 50/60Hz with power current selected through adjustable 300 mA – 15W / 350 mA – 18W / 400/450/500/550/600/ 650/700/750/800/850/900 mA – 15W. switch. 0/1-10V or push dimming  
60.9188



---

Continuous current power supply,  
Mains dimming, leading & trailing edge  
220/240V – 50/60Hz, 300mA-14W /  
350mA-17W / 400mA-19W /  
450/500/600/650/700/750/800/900mA –  
20W  
60.9467

---

Continuous current power supply,  
dimmable Casambi 220/240V-50/60Hz,  
300mA-16W / 350mA-18,5W / 400mA-  
21,5W / 450mA-24W / 500mA-27W /  
600mA-32W / 650mA-35W / 700mA-36W  
/750/800/900/950/1000/1050/1200mA –  
38W  
60.9207

---

Installation Frame No Trim  
08.0166.00