


Light Shadow Pro Ø 60 Adjustable Optic Medium

New

03.9972.GL - Gold

LED lighting module, with low glare, to be inserted in the recessed frames (not included), installation through a bayonet system with interchangeable spots. Remote driver not included.




Main specifications

| | | | |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 857 |
| Lamp category | LED | Mountings | Recessed |
| Power (W) | 10,5W | Environment | Indoor dry location |
| CCT (K) | 2700K | | |
| CRI | 90 | | |

Optical

| | |
|------------------------|-----------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Medium |
| Beam angle (°) | 22 |
| Beam angle C90-270 (°) | 22 |



| | | | |
|-------------|------|-------|------|
| Beam Angle: | 22° | | |
| | h(m) | E(lx) | D(m) |
| 1 | 5870 | 0.38 | |
| 2 | 1468 | 0.77 | |
| 3 | 652 | 1.15 | |
| 4 | 367 | 1.54 | |
| 5 | 235 | 1.92 | |

Luminous flux luminaire
857 lm

Electrical

| | | | |
|--------------|---|------------------|-----|
| Current (mA) | 300 | Insulation class | III |
| Dimmable | Yes | | |
| Driver | Remote excluded | | |
| Driver type | Non Dimmable, Dimmable DALI 2, Dimmable, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1, Mains Cut Dimming | | |
| Emergency | Without | | |

Physical

| | | | |
|---------------------|------------|--------------------|-----|
| Color | Gold | Rotation (°) | 355 |
| Orientation | Adjustable | Spot diameter (mm) | 60 |
| Recessed depth (mm) | 93 | | |
| Weight (kg) | 0.22 | | |
| Tilt (°) | 30 | | |



Light Shadow Pro Ø 60 Adjustable Optic Medium



Installation Frame No Trim
08.0166.00



Continuous current supply source 240V – 50/60Hz with dimmable DALI 2, push dimming. 300mA-16W / 350mA-18W / 400mA-21W / 500mA-27W / 600mA-32W / 650mA-35W
700/750/800/900/950/1000/1050mA-38W
60.9186



Continuous current power supply of 13-20W, 110/240V – 50/60Hz with power current selected through adjustable 300 mA – 15W / 350 mA – 18W / 400/450/500/550/600/ 650/700/750/800/850/900 mA – 15W. switch. 0/1-10V or push dimming
60.9188



Installation Frame Trim
08.0164.40



Installation Frame Trim
08.0164.14



Continuous current power supply, Mains dimming, leading & trailing edge 220/240V – 50/60Hz, 300mA-14W / 350mA-17W / 400mA-19W / 450/500/600/650/700/750/800/900mA – 20W
60.9467



Continuous current power supply,
dimmable Casambi 220/240V-50/60Hz,
300mA-16W / 350mA-18,5W / 400mA-
21,5W / 450mA-24W / 500mA-27W /
600mA-32W / 650mA-35W / 700mA-36W
/750/800/900/950/1000/1050/1200mA –
38W
60.9207

Non dimmable continuous current
power supply of 220/240V – 50/60Hz
with power current selected through
adjustable with switch 200 mA – 8,5W /
300 mA – 13W / 350 mA – 15W / 400 mA
– 17,5W / 450 mA – 19,5W / 500 mA –
22W
60.9160

Continuous current power supply, 0/1-
10V dimmable, 220/240V – 50/60Hz,
300mA-16W / 350mA-18W / 400mA-21W
/ 500mA-27W / 600mA-32W / 650mA-
35W /
700/750/800/900/950/1000/1050mA-36W
60.9439