



Light Shadow Pro Ø 60 Adjustable Optic Spot

New

03.9971.GL - Gold

LED lighting module, with low glare, to be inserted in the recessed frames (not included), installation through a bayonet system with interchangeable spots. Remote driver not included.




Main specifications

Number of heads	1	Net lumen (lm)	672
Lamp category	LED	Mountings	Recessed
Power (W)	10,5W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	16
Beam angle C90-270 (°)	16



Beam Angle:	16°		
	h(m)	E(lx)	D(m)
1	7691	0.28	
2	1923	0.56	
3	855	0.84	
4	481	1.12	
5	308	1.40	

Luminous flux luminaire
672 lm

Electrical

Current (mA)	300	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Non Dimmable, Dimmable DALI 2, Dimmable, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1, Mains Cut Dimming		
Emergency	Without		

Physical

Color	Gold	Rotation (°)	355
Orientation	Adjustable	Spot diameter (mm)	60
Recessed depth (mm)	93		
Weight (kg)	0.22		
Tilt (°)	30		

Note

Preliminary photometries.



Light Shadow Pro Ø 60 Adjustable Optic Spot



Installation Frame Trim
08.0164.40



Installation Frame Trim
08.0164.14



Installation Frame No Trim
08.0166.00



Continuous current power supply,
Mains dimming, leading & trailing edge
220/240V – 50/60Hz, 300mA-14W /
350mA-17W / 400mA-19W /
450/500/600/650/700/750/800/900mA –
20W
60.9467



Continuous current power supply of
13-20W, 110/240V – 50/60Hz with power
current selected through adjustable
300 mA – 15W / 350 mA – 18W /
400/450/500/550/600/
650/700/750/800/850/900 mA – 15W.
switch. 0/1-10V or push dimming
60.9188



Continuous current power supply,
dimmable Casambi 220/240V-50/60Hz,
300mA-16W / 350mA-18,5W / 400mA-
21,5W / 450mA-24W / 500mA-27W /
600mA-32W / 650mA-35W / 700mA-36W
/750/800/900/950/1000/1050/1200mA –
38W
60.9207



Non dimmable continuous current



Continuous current power supply, 0/1-



Continuous current supply source 240V

adjustable with switch 200 mA – 8,5W /	/ 500mA-27W / 600mA-32W / 650mA-	400mA-21W / 500mA-27W / 600mA-32W
300 mA – 13W / 350 mA – 15W / 400 mA	35W /	/ 650mA-35W
– 17,5W / 450 mA – 19,5W / 500 mA –	700/750/800/900/950/1000/1050mA-36W	700/750/800/900/950/1000/1050mA-38W
22W	60.9439	60.9186
60.9160		